



Features

- High current gain
- Low collector-emitter saturation voltage

HF

Mechanical Data

- Case: SOT -323
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-323

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC856A/BW	SOT-323	3000 pcs / Tape & Reel	3A/3B
BC857A/B/CW	SOT-323	3000 pcs / Tape & Reel	3E/3F/3G
BC858A/B/CW	SOT-323	3000 pcs / Tape & Reel	3J/3K/3L

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	BC856W	BC857W	BC858W	Unit
Collector-Base Voltage	V _{CBO}	-80	-50	-30	V
Collector-Emitter Voltage	V _{CEO}	-65	-45	-30	V
Emitter-Base Voltage	V _{EBO}	-5	-5	-5	V
Collector Current (Continuous)	I _C	-100			mA
Collector Current (Peak)	I _{CM}	-200			mA
Base Current (Peak)	I _{BM}	-200			mA

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T _A = 25°C)	P _D	200	mW
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	387	°C/W
Thermal Resistance Junction-to-Case ^{*1}	R _{θJC}	199	°C/W
Thermal Resistance Junction-to-Lead ^{*1}	R _{θJL}	264	°C/W
Operating Junction Temperature	T _J	-65 ~ +150	°C
Storage Temperature Range	T _{STG}	-65 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm * 15mm * 1mm FR4-epoxy P.C.B

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage BC856W	$V_{(BR)CBO}$	$I_C = -10\mu\text{A}, I_E = 0$	-80	-	-	V
Collector-Base Breakdown Voltage BC857W			-50	-	-	
Collector-Base Breakdown Voltage BC858W			-30	-	-	
Collector-Emitter Breakdown Voltage BC856W	$V_{(BR)CEO}$	$I_C = -10\text{mA}, I_B = 0$	-65	-	-	V
Collector-Emitter Breakdown Voltage BC857W			-45	-	-	V
Collector-Emitter Breakdown Voltage BC858W			-30	-	-	V
Emitter-Base Breakdown Voltage BC856W	$V_{(BR)EBO}$	$I_E = -1\mu\text{A}, I_C = 0$	-5	-	-	V
Emitter-Base Breakdown Voltage BC857W			-5	-	-	V
Emitter-Base Breakdown Voltage BC858W			-5	-	-	V
Collector Cut-off Current	I_{CBO}	$V_{CB} = -30\text{V}, I_E = 0$	-	-	-15	nA
Emitter-base Cut-off Current	I_{EBO}	$V_{EB} = -5\text{V}, I_C = 0$	-	-	-100	nA
DC Current Gain BC856/857/858AW	h_{FE}	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	125	-	250	-
DC Current Gain BC856/857/858BW			220	-	475	-
DC Current Gain BC857/858CW			420	-	800	-
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-	-0.3	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-	-0.65	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = -10\text{mA}, I_B = -0.5\text{mA}$	-	-0.70	-	V
		$I_C = -100\text{mA}, I_B = -5\text{mA}$	-	-0.85	-	V
Base-Emitter Voltage	$V_{BE(ON)}$	$V_{CE} = -5\text{V}, I_C = -2\text{mA}$	-0.6	-	-0.75	V
		$V_{CE} = -5\text{V}, I_C = -10\text{mA}$	-	-	-0.82	V
Transition Frequency	f_T	$V_{CE} = -5\text{V}, I_C = -10\text{mA}$ $f = 100\text{MHz}$	100	-	-	MHz
Collector Capacitance	C_C	$V_{CB} = -10\text{V}, I_E = I_C = 0$ $f = 1\text{MHz}$	-	4.5	-	pF

Ratings and Characteristic Curves-BC856/857/858AW (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C




Fig 4 $V_{BE(on)}$ vs. I_C

Ratings and Characteristic Curves-BC856/857/858BW (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_c




Fig 2 $V_{CE(sat)}$ vs. I_c




Fig 3 $V_{BE(sat)}$ vs. I_c




Fig 4 $V_{BE(on)}$ vs. I_c

Ratings and Characteristic Curves-BC857/858CW (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C






Fig 4 $V_{BE(on)}$ vs. I_C

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.