


Features

- Advanced Shielded-Gate Trench technology
- Low on-resistance
- Fast switching speed
- Low thermal resistance
- HBM: JESD22-A114-B: 1B

HF



Mechanical Data

- Case: TO-251, TO-252
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



TO-251

TO-252

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL055N06TI	TO-251	80 pcs / Tube	055N06TI
BL055N06TD	TO-252	80 pcs / Tube or 2500 pcs / Tape & Reel	055N06TD

Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	60	V
Gate-to-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ($T_C = 25^\circ\text{C}$)	I_D	98	A
Continuous Drain Current ($T_C = 100^\circ\text{C}$)		62	A
Continuous Drain Current ($T_A = 25^\circ\text{C}$) ^{*1}		17	A
Continuous Drain Current ($T_A = 100^\circ\text{C}$) ^{*1}		10.7	A
Pulsed Drain Current ($t_p = 10\mu\text{s}$, $T_C = 25^\circ\text{C}$)	I_{DM}	392	A
Single Pulse Avalanche Energy ^{*3}	E_{AS}	80	mJ
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	96	W
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	-	-	1.3	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	-	-	45	$^\circ\text{C/W}$

Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	60	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 48V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = 10V, I _D = 30A	-	5	5.5	mΩ
		V _{GS} = 4.5V, I _D = 20A	-	7.5	9	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	1	1.8	2.5	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	2.2	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 30V f = 1.0MHz	-	1527	-	pF
C _{OSS}	Output Capacitance		-	638	-	
C _{RSS}	Reverse Transfer Capacitance		-	16	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time	V _{DD} = 30V V _{GS} = 15V I _D = 15A R _G = 3.3Ω	-	17	-	ns
t _r	Turn-on Rise Time		-	19	-	
t _{d(OFF)}	Turn-Off Delay Time		-	45	-	
t _f	Turn-Off Fall Time		-	10	-	
Q _G	Total Gate-Charge	V _{DD} = 48V V _{GS} = 10V I _D = 15A	-	30.7	-	nC
Q _{GS}	Gate to Source Charge		-	4.2	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	9.3	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _S = 5A, V _{GS} = 0V	-	0.8	1.2	V
t _{rr}	Reverse Recovery Time	I _F = 30A, V _{GS} = 0V di/dt = 100A/μs	-	41	-	ns
Q _{rr}	Reverse Recovery Charge		-	37	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The data tested by pulsed, pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- The E_{AS} data shows Max. rating. The test condition is $V_{DD} = 25V, V_{GS} = 10V, L = 0.5mH$

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature






Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature

Package Outline Dimensions (Unit: mm)




TO-251		
Dimension	Min.	Max.
A	5.05	5.65
B	5.80	6.40
C	6.25	6.85
D	2.20	2.40
E	0.40	0.60
F	11.00	11.60
G	5.05	5.65
H	2.10	2.50
I	0.70	0.90
J	4.00	4.40
K	0.40	0.60



TO-252		
Dimension	Min.	Max.
A	5.05	5.65
B	5.80	6.40
C	6.25	6.85
D	2.20	2.40
E	0.40	0.60
F	9.71	10.31
G	5.05	5.65
H	2.10	2.50
I	0.70	0.90
J	0.50	0.70
K	0.40	0.60

Mounting Pad Layout (Unit: mm)

TO-252



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.