

Features

- N-Channel switch with low $R_{DS(on)}$
- Operated at low logic level gate drive



HF

Typical Applications

- Load/Power Switching
- Interfacing Switching
- Battery Management for Ultra Small Portable Electronics
- Logic Level Shift

Mechanical Data

- Case: SOT-563
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte Tin-Plated Leads, Solderability-per MIL-STD-202, Method 208



SOT-563

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL1012V	SOT-563	3000 pcs / Tape & Reel	1012

Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate -Source Voltage	V_{GS}	± 12	V
Continuous Drain Current	I_D	0.75	A
Power Dissipation ^{*1}	P_D	0.25	W

Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	500	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Case ^{*1}	$R_{\theta JC}$	342	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Lead ^{*1}	$R_{\theta JL}$	280	$^\circ\text{C/W}$
Operating Junction Temperature Range	T_J	$-55 \sim +150$	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	$-55 \sim +150$	$^\circ\text{C}$





Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)





Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	20	-	-	V
I _{DSS}	Drain to Source Leakage Current	V _{DS} = 20V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-body Leakage	V _{GS} = ±12V, V _{DS} = 0V	-	-	±20	μA
On Characteristics ^{*2}						
R _{DS(ON)}	Static Drain-Source On-resistance	V _{GS} = 4.5V, I _D = 0.65A	-	0.25	0.38	Ω
		V _{GS} = 2.5V, I _D = 0.55A	-	0.30	0.45	
		V _{GS} = 1.8V, I _D = 0.45A	-	0.37	0.8	
V _{GS(TH)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	0.35	0.65	1.1	V
Dynamic Characteristics ^{*3}						
C _{ISS}	Input Capacitance	V _{GS} = 0V	-	67	-	pF
C _{OSS}	Output Capacitance	V _{DS} = 10V	-	19	-	
C _{RSS}	Reverse Transfer Capacitance	f = 1.0MHz	-	6	-	
Switching Characteristics ^{*3}						
t _{d(on)}	Turn-on Delay Time	V _{DD} = 10V, I _D = 0.5A V _{GS} = 4.5V, R _G = 1Ω	-	11	-	ns
t _r	Turn-on Rise Time		-	16	-	
t _{d(off)}	Turn-Off Delay Time		-	26	-	
t _f	Turn-Off Fall Time		-	11	-	
Q _g	Total Gate Charge	V _{DD} = 10V	-	1.4	-	nC
Q _{gs}	Gate-Source Charge	I _D = 0.6A	-	0.22	-	
Q _{gd}	Gate-Drain Charge	V _{GS} = 4.5V	-	0.21	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage ^{*1}	I _S = 0.15A, V _{GS} = 0V	-	0.8	1.2	V

Notes:


- 1、 Surface mounted on FR4 board, $t \leq 10$ sec
- 2、 Pulse Test: Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$
- 3、 Guaranteed by design, not subject to production

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)






Package Outline Dimensions (Unit: mm)



SOT-563		
Dimension	Min.	Max.
A	1.500	1.700
B	1.100	1.300
C	0.525	0.600
D	0.170	0.270
E	0.100	0.300
G	0.450	0.550
H	0.000	0.050
J	0.090	0.160
K	1.500	1.700

Mounting Pad Layout (Unit: mm)

SOT-563



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.