

Features

- Reliable and Rugged
- Green device available



HF

Applications

- Synchronous Rectification
- Motor Control
- Portable equipment application

Mechanical Data

- Case: PDFN5x6-8LC
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



PDFN5×6-8LC

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
GBLH4408-5DL8	PDFN5x6-8LC	5000 pcs / Tape & Reel	GBLH4408

Maximum Ratings (@ T_C = 25°C unless otherwise specified)

Parameter	Symbol	TR1	TR2	Unit
Drain-to-Source Voltage	V _{DSS}	40	-40	V
Gate-to-Source Voltage	V _{GSS}	±20	±20	V
Continuous Drain Current (T _C = 25°C)	I _D	56	-33	A
Continuous Drain Current (T _C = 100°C)		40	-23	A
Continuous Drain Current (T _A = 25°C) *1		16	-9.3	A
Continuous Drain Current (T _A = 100°C) *1		11	-6.6	A
Single Pulse Avalanche Energy *3	E _{AS}	18	66	mJ
Pulsed Drain Current (t _p = 10μs, T _C = 25°C)	I _{DM}	280	-165	A
Power Dissipation (T _C = 25°C)	P _D	47	47	W
Operating Junction Temperature Range	T _J	-55 ~ +175		°C
Storage Temperature Range	T _{STG}	-55 ~ +175		°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	-	-	3.2	$^{\circ}\text{C}/\text{W}$
Thermal Resistance Junction-to-Air ^{*1}	$R_{\theta JA}$	-	-	40	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics-TR1 (@ $T_A = 25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V_{DSS}	Drain-Source Breakdown Voltage	$V_{GS} = 0\text{V}, I_D = 250\mu\text{A}$	40	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 40\text{V}, V_{GS} = 0\text{V}$	-	-	1	μA
I_{GSS}	Gate-Body Leakage Current	$V_{GS} = \pm 20\text{V}, V_{DS} = 0\text{V}$	-	-	± 100	nA
On Characteristics						
$R_{DS(ON)}$	Drain-Source On-resistance ^{*2}	$V_{GS} = 10\text{V}, I_D = 12\text{A}$	-	8	9	m Ω
		$V_{GS} = 4.5\text{V}, I_D = 10\text{A}$	-	13	16	m Ω
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	1	1.7	2.5	V
R_G	Gate Resistance	$V_{GS} = 0\text{V}, f = 1\text{MHz}$	-	3.4	-	Ω
Dynamic Characteristics						
C_{ISS}	Input Capacitance	$V_{GS} = 0\text{V}$ $V_{DS} = 15\text{V}$ $f = 1.0\text{MHz}$	-	687	-	pF
C_{OSS}	Output Capacitance		-	135	-	
C_{RSS}	Reverse Transfer Capacitance		-	128	-	
Switching Characteristics						
$t_{d(ON)}$	Turn-on Delay Time ^{*4}	$V_{DD} = 20\text{V}, V_{GS} = 4.5\text{V}$ $R_G = 3.3\Omega$ $I_D = 20\text{A}$	-	9	-	ns
t_r	Turn-on Rise Time ^{*4}		-	49	-	
$t_{d(OFF)}$	Turn-Off Delay Time ^{*4}		-	20	-	
t_f	Turn-Off Fall Time ^{*4}		-	6	-	
Q_G	Total Gate-Charge	$V_{DD} = 20\text{V}$	-	9.7	-	nC
Q_{GS}	Gate to Source Charge	$V_{GS} = 4.5\text{V}$	-	2.1	-	
Q_{GD}	Gate to Drain (Miller) Charge	$I_D = 12\text{A}$	-	5.8	-	
Source-Drain Diode Characteristics						
V_{SD}	Diode Forward Voltage ^{*2}	$I_{SD} = 1\text{A}, V_{GS} = 0\text{V}$	-	0.7	1	V
t_{rr}	Reverse Recovery Time	$I_F = 15\text{A}, V_{GS} = 0\text{V}$	-	21	-	ns
Q_{rr}	Reverse Recovery Charge	$di/dt = 100\text{A}/\mu\text{s}$	-	9	-	nC

Electrical Characteristics-TR2 (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	-40	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = -40V, V _{GS} = 0V	-	-	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Drain-Source On-resistance *2	V _{GS} = -10V, I _D = -10A	-	18	25	mΩ
		V _{GS} = -4.5V, I _D = -8A	-	24	36	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	-1	-1.5	-2.5	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	12	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = -20V f = 1.0MHz	-	2307	-	pF
C _{OSS}	Output Capacitance		-	184	-	
C _{RSS}	Reverse Transfer Capacitance		-	152	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time *4	V _{DD} = -20V V _{GS} = -10V R _L = 1.6Ω I _D = -1A	-	10	-	ns
t _r	Turn-on Rise Time *4		-	24	-	
t _{d(OFF)}	Turn-Off Delay Time *4		-	40	-	
t _f	Turn-Off Fall Time *4		-	9	-	
Q _G	Total Gate-Charge	V _{DD} = -20V V _{GS} = -10V I _D = -8A	-	46	-	nC
Q _{GS}	Gate to Source Charge		-	6.5	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	7.3	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage *2	I _{SD} = -8A, V _{GS} = 0V	-	-0.9	-1.2	V
t _{rr}	Reverse Recovery Time	I _F = -10A, V _{GS} = 0V di/dt = 100A/μs	-	48	-	ns
Q _{rr}	Reverse Recovery Charge		-	29	-	nC

Notes:

- The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
- The data tested by pulsed, pulse width ≤ 300μs, duty cycle ≤ 2%
- The E_{AS} data shows Max. rating. N: The test condition is V_{DD} = 20V, V_{GS} = 10V, L = 0.5mH
P: The test condition is V_{DD} = -20V, V_{GS} = -10V, L = 0.5mH
- Guaranteed by design, not subject to production

Ratings and Characteristics Curves-TR1 (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized V_{GS(th)} vs. Junction Temperature




Fig 13 Safe Operation Area




Fig 14 Maximum transient thermal impedance

Ratings and Characteristics Curves-TR2 (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized $V_{GS(th)}$ vs. Junction Temperature




Fig 13 Safe Operation Area






Fig 14 Maximum transient thermal impedance

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.