



Features

- Super Low Gate Charge
- Green Device Available
- Excellent CdV/dt Effect Decline
- Advanced High Cell Density Trench Technology

HF

Mechanical Data

- Case: SOP-8
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



SOP-8

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
GBLN3302-S8	SOP-8	4000 pcs / Tape & Reel	GBLN3302

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	V _{DSS}	30	V
Gate-to-Source Voltage	V _{GSS}	±20	V
Continuous Drain Current (T _A = 25°C) *1, 2	I _D	4.5	A
Continuous Drain Current (T _A = 70°C) *1, 2		3.5	A
Pulsed Drain Current *3	I _{DM}	18	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation (T _A = 25°C)	P _D	1.7	W
Operating Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Electrical Characteristics-TR1 (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 30V, V _{GS} = 0V, T _J = 25°C	-	-	0.5	μA
		V _{DS} = 30V, V _{GS} = 0V, T _J = 55°C	-	-	10	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±20V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DS(ON)}	Static Drain-Source On-resistance *3	V _{GS} = 10V, I _D = 3.5A	-	-	47	mΩ
		V _{GS} = 4.5V, I _D = 2.8A	-	-	65	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	1	-	3	V
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 15V f = 1.0MHz	-	420	-	pF
C _{OSS}	Output Capacitance					
C _{RSS}	Reverse Transfer Capacitance					
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time	V _{GS} = 10V V _{DD} = 15V I _D = 1A R _G = 3.3Ω	-	2	-	ns
t _r	Turn-on Rise Time					
t _{d(OFF)}	Turn-Off Delay Time					
t _f	Turn-Off Fall Time					
Q _G	Total Gate-Charge	V _{DD} = 15V V _{GS} = 4.5V I _D = 1A	-	5	-	nC
Q _{GS}	Gate to Source Charge					
Q _{GD}	Gate to Drain (Miller) Charge					
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _{SD} = 1A, V _{GS} = 0V	-	-	1.2	V

Notes:

1. Surface Mounted on FR4 Board, t_s ≤ 5 sec.
2. Pulse width limited by maximum junction temperature.
3. Pulse test: PW ≤ 300 us duty cycle ≤ 2%.

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance vs. G-S Voltage




Fig.3 Forward Characteristics of Reverse Diode




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J




Fig.7 Capacitance






Fig.8 Safe Operating Area

Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)



Important Notice

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.